



Sasol Engine Oil Multigrade RI4 15W-40

ENGINE OIL, MULTIGRADE, SAE 15W-40

Description

Sasol Engine Oil Multigrade RI4 15W-40 is a multigrade designed and suitable for heavy duty, internal combustion engine oil formulated from quality base stocks and additives.

Application

Sasol Engine Oil Multigrade RI4 15W-40 is intended for all naturally aspirated and turbocharged petrol and diesel engines for on and off highway applications.

Sasol Engine Oil Multigrade RI4 15W-40 offers high levels of engine wear protection in the critical areas of valve train, piston ring and cylinder liners. The enhanced detergency and dispersancy of Sasol Engine Oil Multigrade RI4 15W-40 prevent formation of harmful deposits in the areas of the engine, including sludge and piston deposit. The optimized detergent and dispersant additive system keeps engines cleaner than previous generation oils.

Features and Benefits

Sasol Engine Oil Multigrade RI4 15W-40 has the following features and benefits:

- Excellent deposit control
- Excellent acid and corrosion control
- Reduced engine wear
- Good with low emission engines
- good fuel saving properties

Product Specifications

| | |
|---------------------------|----------------------------|
| ACEA A3, B3, E3, E7 | MAN 3275-1 |
| EO-M Plus | Mercedes-Benz 228.3 |
| API CI-4, CH-4, CG-4, SL | SABS 1842 & 1843 |
| Cummins CES 20078, 77, 76 | Volvo VDS-3 |
| MTU Type 2 | Caterpillar ECF-2, ECF-1-A |

Typical Characteristics

| Property | Units | Typical | ASTM | IP |
|--------------------|--------------------|-------------|-------|-----|
| Viscosity | | | D445 | 71 |
| @ 100°C | mm ² /s | 15.4 | | |
| @ 40°C | mm ² /s | 109 | | |
| Apparent Viscosity | mPa.s @ -15°C | 3000 | D5293 | |
| Viscosity Index | | 135 | D2270 | 226 |



| | | | | |
|--------------------------|-------------------|------------|----------------------------|-----|
| Pour Point | °C | -39 | D97 | 15 |
| Flash Point (COC) | °C | 225 | D92 | 36 |
| Evaporative Loss (Noack) | % m/m | 11 | CEC L-40-T-87 or DIN 51581 | |
| Density @ 20°C | kg/m ³ | 883 | D4052 | 365 |
| Sulphated Ash | % m/m | 1.2 | D874 | 163 |
| Total Base Number | mg KOH/g | 11 | D2896 | 276 |

Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

| Product Code | Pack Size |
|---------------------|------------------|
| | 1x500 ml |
| | 20x500 ml |
| | 1x5 L |
| | 4x5 L |
| | 20 L |
| | 210 L |
| | Bulk |